



Sciencetech 2501A Optical Fiber Communication TechBook demonstrate simplex method of transmitting information from one place to another by sending pulses of light through an Optical fiber. The TechBook demonstrates the properties of Simplex Analog and Digital Transceiver, characteristics of Fiber Optics cable, Modulation / Demodulation techniques, Bit Error Rate measurement and observation of Eye Pattern. A large number of experiments are included in the workbook and many more can be performed using Sciencetech 2501A.

Features

- Simplex Analog and Digital Transceiver
- 660 nm channel with Transmitter & Receiver
- AM-FM-PWM modulation / demodulation
- On board Function Generator
- On board Clock & Data Generator
- On board Bit Error Counter
- Crystal controlled Clock
- Functional blocks indicated on-board mimic
- Input-output & test points provided on board
- On board voice link
- Built in DC Power Supply
- Numerical Aperture measurement jig and mandrel for bending loss measurement
- Switched faults on Transmitter & Receiver

Scope of Learning

- Setting up Fiber Optic Analog & Digital Link
- AM system using Analog & Digital Input Signals
- Frequency Modulation System
- Pulse Width Modulation System
- Study of Propagation Loss in Optical Fiber
- Study of Bending Loss
- Measurement of Numerical Aperture
- Characteristics of Fiber Optic Communication Link
- Setting of Fiber Optic Voice Link using AM, FM & PWM
- Study of switched faults in AM, FM & PWM System
- Propagation loss using Optical Power Meter
- V-I Characteristics of LED (E - O converter)
- Characteristics of Photo Detector
- Effect of EMI on Optical Communication
- Measurement of Bit Error Rate
- Study of Eye Pattern

Technical Specifications

Transmitter	: 1 no., Fiber Optic LED having peak wavelength of emission 660 nm
Receiver	: 1 no., Fiber Optic Photodetector
Modulation Techniques	: 1. AM 2. FM 3. PWM
Drivers	: 1 no. with Analog & Digital modes
Clock	: Crystal controlled Clock 4.096 MHz
PLL Detector	: 1 no.
AC Amplifier	: 1 no.
Comparator	: 1 no.
Filters	: 1 no. 4th order Butterworth, 3.4 KHz cut-off frequency
Analog Band Width	: 350 KHz
Digital Band Width	: 2.5 MHz
Function Generator	: 1 KHz Sine wave (Amplitude adjustable)
1 KHz Square wave (TTL)	
Clock Generator	: 64 KHz/128 KHz/256 KHz (TTL)
Data Generator	: 15 Bit
Noise Generator	: Variable level
Bit Error Counter	: 4 digits, 7 segment display
Voice Link	: F. O. voice link using microphone & speaker (built in)
Switched Faults	: 4 in Transmitter & 4 in Receiver
Fiber Optic Cable	: Connector type Standard SMA
Cable Type	: Step indexed multimode PMMA plastic cable
Core Refractive Index	: 1.492
Clad Refractive Index	: 1.406
Numerical Aperture	: Better than 0.5
Acceptance Angle	: Better than 60 deg.
Fiber Diameter	: 1000 microns
Outer Diameter	: 2.2 mm
Fiber Length	: 0.5 m & 1 m
Test Points	: 34 nos
Inter connections	: 2 mm sockets
Dimensions (mm)	: W 326 × D 252 × H 52
Weight	: 1 Kg approximately
Operating conditions	: 0-40°C, 80% RH
Power Supply	: 110-220 V, ±10%, 50/60 Hz
Power Consumption	: 3 VA approximately
Included Accessories	: NA Measurement jig, Mandrel, Fiber cables, Microphone, Headphone, Set of Patch cords
Optional Accessories	: Optical Power Meter, 5 meter fiber cable, 10 meter fiber cable.