



Sciencetech TechBooks are compact and user friendly learning platforms to provide a modern, portable, comprehensive and practical way to learn Technology. Each TechBook is provided with detailed Multimedia learning material which covers basic theory, step by step procedure to conduct the experiment and other useful information.

Frequency Division Multiplexer/Demultiplexer TechBook Sciencetech 2211 demonstrates FDM technique. It basically fulfills the need for communication of two different inputs through a single channel by Frequency Division Multiplexing method. Sciencetech 2211 has the provision for onboard modulating signal as well as voice input. For reducing the complexity same carriers are used for demodulation also. In actual FDM communication method carrier is obtained through the modulated output only. But the basic concept remains the same. DSB-SC modulation technique is used for modulation and demodulation.

Features

- Self contained and easy to operate
- Two variable modulating (sinusoidal) input channels with provision of voice inputs
- Two DSBSC modulators for frequency band translation of two test signals
- Two Carrier Generators
- Two sets of audio input amplifier
- One adder/transmission amplifier
- Two Demodulators
- Two low pass filters for smooth output
- 2 Sets of audio O/P amplifier

Scope of Learning

Study of:

- Frequency Division Multiplexing / Demultiplexing with sinusoidal & audio inputs
- Fourier Spectrum of FDM
- DSBSC Modulation/Demodulation

Technical Specifications

Crystal Frequency	: 4.096 MHz
Carrier Generator	: Sine wave 100 KHz & 200 KHz
Modulating Input Frequency	: Sine wave 200 Hz-10 KHz (variable)
Audio Input Amplifier	: Gain of 100 (approx.)
Modulator / Demodulator	: DSBSC Modulator/Demodulator
Low Pass Filters	: Second Order Butterworth filters with a cut off frequency of 10 KHz
Audio Output Amplifier	: Output Amplifier with a gain of 20
Test points	: 30 nos
Interconnection	: 2mm banana socket
Power Supply	: 220V/110V, 50 Hz / 60 Hz
Power Consumption	: 3 VA (approx.)
Dimensions (mm)	: W 326 x D 252 x H 52
Weight	: 3.5 Kg. (approximately)
Operating Conditions	: 0-40°C, 85% RH
Product Tutorial	: Online on www.SciencetechLearning.com
Included Accessories :	
Patch cord 16"	: 15 nos.
Headphone	: 2 nos.
Microphone	: 2 nos.
Mains cord	: 1 no.